



CSF

TECHNICAL


Materials of Optics	PC
Materials of Housing	Aluminium
Light Source	SMD (SCDM <3)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@4000K	110lm/W
CRI	≥80
Beam Angle(°)	120°
UGR	-
Lifetime(hr)	>50,000h
Product Finishing	White/Black

FEATURES & BENEFITS

LED Driver	Built-in
Dimming Option	DALI/1-10V
Functions	Adjustable Power
Ingress Protection (IP Rating)	IP40
Impact Resistance (IK Rating)	-
Power Factor (PF)	≥0.9
Certification	



ACCESSORIES & DIMENSIONS ES



ACC-AL99-XX-XT-50



ACC-AL99-XK-51



ACC-AL99-XK-52

MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBmm)	LUMEN(±5%)	N.W/pc(kgs)
CSF-12-24	30W	AC200-240V	300x58	3300lm	1.6
CSF-16-40	40W	AC200-240V	400x86	4300lm	3.20
CSF-24-60	60W	AC200-240V	600x86	6700lm	6.90
CSF-32-75	75W	AC200-240V	800x86	8000lm	11.00
CSF-40-100	100W	AC200-240V	1000x86	10700lm	16.20