



CSU

TECHNICAL

| | |
|---------------------------|-------------------------|
| Materials of Optics | PC |
| Materials of Housing | PC |
| Light Source | SMD (SCDM <3) |
| Color Temperature | 3000K/4000K/5000K/5700K |
| Luminous Efficiency@4000K | 105lm/W |
| CRI | ≥80/90 |
| Beam Angle(°) | 120° |
| UGR | - |
| Lifetime(hr) | >50,000h |
| Product Finishing | White |


FEATURES & BENEFITS

| | |
|--------------------------------|------------|
| LED Driver | Built-in |
| Dimming Option | Dali/1-10V |
| Functions | - |
| Ingress Protection (IP Rating) | IP65 |
| Impact Resistance (IK Rating) | IK09 |
| Power Factor (PF) | ≥0.9 |

Certification



ACCESSORIES & DIMENSIONS



MODEL REF.

Standard CCT 4000K

| CODE | WATT | INPUT VOLTAGE(V) | SIZE(AxBxCmm) | LUMEN(±5%) | N.W/pc(kgs) |
|--------|------|------------------|---------------|------------|-------------|
| CSU-18 | 18W | AC220-240V | 320x85 | 2100 | 1.8 |
| CSU-25 | 25W | AC220-240V | 320x85 | 2700 | 1.8 |