



## CWP

### TECHNICAL


Materials of Optics	PC
Materials of Housing	PC
Light Source	SMD (SDCM <6)
Color Temperature	3000K/4000K/5000K/5700K
Luminous Efficiency@4000K	120 Lum/W
CRI	≥80
Beam Angle(°)	90 deg
UGR	-
Lifetime(hr)	>50,000h
Product Finishing	Grey



### FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Triac/ DALI/ 0-10V
Functions	Power adjustable for different light outputs
Ingress Protection (IP Rating)	IP65
Impact Resistance (IK Rating)	IK09
Power Factor (PF)	≥0.9
Certification	SAA/ RoHS/ CE

### ACCESSORIES & DIMENSIONS



### MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	LUMEN(±5%)	N.W/pc(kgs)
CWP-60-12	12W	220-240V AC	631x86x70	1440	1.85
CWP-60-17	17W	220-240V AC	631x86x70	2040	1.85
CWP-120-25	25W	220-240V AC	1231x86x70	3000	1.85
CWP-120-40	40W	220-240V AC	1231x86x70	4800	1.85