



DDL

TECHNICAL

Materials of Optics	PC + White Powdered Aluminium
Materials of Housing	Trimmed sheet steel, chemically treated and electrostatically powder coated
Light Source	SMD (SCDM <3)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@4000K	120 Lum/W
CRI	>80
Beam Angle(°)	90 deg
UGR	
Lifetime(hr)	L80/B10 > 90000hrs @ 25°C
Product Finishing	White

FEATURES & BENEFITS

LED Driver	Built-Out
Dimming Option	Dali/1-10V
Functions	Power adjustable for different light outputs
Ingress Protection (IP Rating)	IP44/IP54/IP65
Impact Resistance (IK Rating)	IK03
Power Factor (PF)	> 0.90

Certification



MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	LUMEN(±5%)	N.W/pc(kgs)
DDL-13	13W	220-240V AC	170x60x160	1500	0.8
DDL-18	18W	220-240V AC	170x60x160	2192	0.8
DDL-21	21W	220-240V AC	220x60x210	2632	1.10
DDL-29	29W	220-240V AC	220x60x210	3550	1.20

ACCESSORIES & DIMENSIONS ES

