



DLB

TECHNICAL


Materials of Optics	PC
Materials of Housing	Aluminium
Light Source	SMD (SCDM <3)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@4000K	100lm/W
CRI	>80
Beam Angle(°)	90 deg
UGR	
Lifetime(hr)	> 50,000h
Product Finishing	White

FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Dali/1-10V
Functions	
Ingress Protection (IP Rating)	IP54
Impact Resistance (IK Rating)	IK01
Power Factor (PF)	> 0.90
Certification	



ACCESSORIES & DIMENSIONS ES



MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	LUMEN(±5%)	N.W/pc(kgs)
DLB-10	10W	220-240V AC	110x30x90	1000	0.25
DLB-13	13W	220-240V AC	110x30x90	1320	0.25
DLB-18	18W	220-240V AC	145x30x120	1980	0.35
DLB-25	25W	220-240V AC	190x30x160	2750	0.50
DLB-35	35W	220-240V AC	225x30x200	3900	0.65
DLB-42	42W	220-240V AC	225x30x200	4750	0.65