



## DLC

### TECHNICAL

Materials of Optics	PC+AL1070+Tempered glass
Materials of Housing	Die Cast Aluminium
Light Source	COB (SCDM <3)
Color Temperature	2700K/ 3000K/ 4000K/ 5000K
Luminous Efficiency@4000K	110lm/W
CRI	≥80
Beam Angle(°)	24/36/38/60 Deg (DL284A)
UGR	-
Lifetime(hr)	>50,000h
Product Finishing	White


### FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Triac/ DALI/ 0-10V
Functions	-
Ingress Protection (IP Rating)	IK65
Impact Resistance (IK Rating)	IK06/ IK08(DL284A)
Power Factor (PF)	≥0.9

#### Certification



### ACCESSORIES & DIMENSIONS



### MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBmm)	CUT-OUT(mm)	LUMEN(±5%)	N.W/pc(kgs)
DLC-10	10W	AC220-240V	110x51x90	90-95	1050	0.34
DLC-13	13W	AC220-240V	110x51x90	90-95	1350	0.34
DLC-18	18W	AC220-240V	150x64x140	125-140 / 125-135	1950	0.62/0.72
DLC-25	25W	AC220-240V	150x64x140	125-140 / 125-135	2750	0.62/0.72
DLC-30	30W	AC220-240V	172x69x165	150-160 / 150-160	1950	0.79/0.90
DLC-35	35W	AC220-240V	235x81x220	200-220 / 200-210	3850	1.27/1.45