



## DLD

### TECHNICAL

|                           |                            |
|---------------------------|----------------------------|
| Materials of Optics       | PC                         |
| Materials of Housing      | Aluminium                  |
| Light Source              | SMD (SCDM <3)              |
| Color Temperature         | 3000K/ 4000K/ 5000K/ 5700K |
| Luminous Efficiency@4000K | 100lm/W                    |
| CRI                       | >80                        |
| Beam Angle(°)             | 90 deg                     |
| UGR                       |                            |
| Lifetime(hr)              | > 50,000h                  |
| Product Finishing         | White                      |


### FEATURES & BENEFITS

|                                |            |
|--------------------------------|------------|
| LED Driver                     | Built-out  |
| Dimming Option                 | Dali/1-10V |
| Functions                      |            |
| Ingress Protection (IP Rating) | IP54       |
| Impact Resistance (IK Rating)  | IK06       |
| Power Factor (PF)              | > 0.90     |

Certification



### ACCESSORIES & DIMENSIONS ES



### MODEL REF

Standard CCT 4000K

| CODE   | WATT | INPUT VOLTAGE(V) | SIZE(AxBxCmm) | LUMEN(±5%) | N.W/pc(kgs) |
|--------|------|------------------|---------------|------------|-------------|
| DLD-10 | 10W  | 220-240V AC      | 110x38x96     | 960        | 0.32        |
| DLD-13 | 13W  | 220-240V AC      | 110x38x96     | 1180       | 0.32        |
| DLD-18 | 18W  | 220-240V AC      | 170x45x140    | 1980       | 0.47        |
| DLD-25 | 25W  | 220-240V AC      | 198x45x160    | 2630       | 0.81        |
| DLD-35 | 35W  | 220-240V AC      | 228x45x20     | 3500       | 0.81        |