

DLG

TECHNICAL

Materials of Optics	PC
Materials of Housing	Aluminium
Light Source	SMD (SCDM <3)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@4000K	100lm/W
CRI	>80
Beam Angle(°)	24,36,60
UGR	< 19
Lifetime(hr)	> 50,000h
Product Finishing	White




FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Dali/1-10V
Functions	-
Ingress Protection (IP Rating)	IP40 IP54
Impact Resistance (IK Rating)	-
Power Factor (PF)	≥0.9

Certification



ACCESSORIES & DIMENSIONS



MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBmm)	LUMEN(±5%)	N.W/pc(kgs)
DLG-10	10W	AC200-240V	95x84x82	1120	0.23
DLG-13	13W	AC200-240V	110x54x90	1300	0.27
DLG-18	18W	AC200-240V	145x78x125	2250	0.48
DLG-25	25W	AC200-240V	172x90x150	2850	0.71
DLG-35	35W	AC200-240V	228x99x200	4000	1.14
DLG-10 (Drop glass)	10W	AC200-240V	172.5x97x125	1012	1.05
DLG-18 (Drop glass)	18W	AC200-240V	172.5x97x125	1980	1.05
DLG-25 (Drop glass)	25W	AC200-240V	197x109x150	2508	1.30
DLG-35 (Drop glass)	35W	AC200-240V	246x118x200	3520	1.80