



## DLI

### TECHNICAL

Materials of Optics	PMMA
Materials of Housing	Die Cast Aluminium
Light Source	COB (SCDM <3)
Color Temperature	2700K/ 3000K/ 4000K/ 5000K
Luminous Efficiency@4000K	100lm/W
CRI	≥ 80/90
Beam Angle(°)	36°/ 60°
UGR	-
Lifetime(hr)	>50,000h
Product Finishing	White


### FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Triac/ DALI/ 0-10V
Functions	-
Ingress Protection (IP Rating)	IP65
Impact Resistance (IK Rating)	-
Power Factor (PF)	≥0.9

Certification



### ACCESSORIES & DIMENSIONS



### MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBmm)	CUT-OUT(mm)	LUMEN(±5%)	N.W/pc(kgs)
DLI-5	5W	AC220-240V	80x30	68-72	530	0.24
DLI-8	8W	AC220-240V	80x30	68-72	8151	0.24
DLI-10	10W	AC220-240V	90x39.3	75-80	1000	0.25
DLI-13	13W	AC220-240V	110x49.4	90-95	1350	0.40