



DLP

TECHNICAL

Materials of Optics	PC
Materials of Housing	Plastic Coated Aluminum
Light Source	SMD (SCDM <3)
Color Temperature	2700K/ 3000K/ 4000K/ 5000K
Luminous Efficiency@4000K	110lm/W
CRI	≥80
Beam Angle(°)	90°
UGR	-
Lifetime(hr)	>50,000h
Product Finishing	White


FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Triac/ DALI/ 0-10V
Functions	-
Ingress Protection (IP Rating)	IP54
Impact Resistance (IK Rating)	IK06/ IK08(DL284A)
Power Factor (PF)	≥0.9

Certification



ACCESSORIES & DIMENSIONS



MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBmm)	CUT-OUT(mm)	LUMEN(±5%)	N.W/pc(kgs)
DLP-10	10W	AC220-240V	110x51x90	90-95	1050	0.34
DLP-13	13W	AC220-240V	110x51x90	90-95	1350	0.34
DLP-18	18W	AC220-240V	150x64x140	125-140 / 125-135	1950	0.62/0.72
DLP-25	25W	AC220-240V	150x64x140	125-140 / 125-135	2750	0.62/0.72
DLP-30	30W	AC220-240V	172x69x165	150-160 / 150-160	1950	0.79/0.90
DLP-35	35W	AC220-240V	235x81x220	200-220 / 200-210	3850	1.27/1.45