



DLQ

TECHNICAL

Materials of Optics	PMMA
Materials of Housing	Die Cast Aluminium
Light Source	COB (SCDM <3)
Color Temperature	2700K/ 3000K/ 4000K/ 5000K
Luminous Efficiency@4000K	105lm/W
CRI	≥ 80/90
Beam Angle(°)	36°/60°
UGR	-
Lifetime(hr)	>50,000h
Product Finishing	White


FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Triac/ DALI/ 0-10V
Functions	-
Ingress Protection (IP Rating)	IP65
Impact Resistance (IK Rating)	-
Power Factor (PF)	≥0.9

Certification



ACCESSORIES & DIMENSIONS ES



MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	CUT-OUT(mm)	LUMEN(±5%)	N.W/pc(kgs)
DLQ-5	5W	AC220-240V	80x80x40	68-72	530	0.22
DLQ-8	8W	AC220-240V	80x80x40	68-72	815	0.22
DLQ-10	10W	AC220-240V	90x90x49	75-80	1000	0.28
DLQ-13	13W	AC220-240V	110x110x64	90-95	1000	0.39