

DLR



TECHNICAL


Materials of Optics	PC+Tempered Glass
Materials of Housing	Die Cast Aluminium
Light Source	SMD (SCDM <3)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@4000K	120 lm/W
CRI	>80
Beam Angle(°)	24/36/45/60 deg
UGR	
Lifetime(hr)	> 50,000h
Product Finishing	White

FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Dali/1-10V
Functions	
Ingress Protection (IP Rating)	IP54
Impact Resistance (IK Rating)	-
Power Factor (PF)	> 0.90
Certification	



ACCESSORIES & DIMENSIONS ES



MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	LUMEN(±5%)	N.W/pc(kgs)
DLR-10	10W	220-240V AC	110x33x90	1250	0.34
DLR-12	12W	220-240V AC	110x53x90	1500	0.34
DLR-18	18W	220-240V AC	145x65x120	2250	0.62/0.72
DLR-25	25W	220-240V AC	190x75x160	3125	0.79/0.90
DLR-33	33W	220-240V AC	190x75x160	3650	0.79/0.90
DLR-42	42W	220-240V AC	225x87x200	4950	1.27/1.45