

DLY

TECHNICAL


Materials of Optics	PC with Glass
Materials of Housing	Die Cast Aluminium
Light Source	COB (SCDM <3)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@4000K	120 Lum/W
CRI	>80
Beam Angle(°)	15/20/24/36/45/60 deg
UGR	-
Lifetime(hr)	>50,000h
Product Finishing	White

FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Triac
Functions	-
Ingress Protection (IP Rating)	IP54
Impact Resistance (IK Rating)	-
Power Factor (PF)	> 0.90
Certification	



ACCESSORIES & DIMENSIONS



MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	LUMEN(±5%)	N.W/pc(kgs)
DLY-8	8W	220-240V AC	80x32 68-75	960	0.24
DLY-10	10W	220-240V AC	110x47 90-95	1200	0.38
DLY-13	13W	220-240V AC	110x47 90-95	1340	0.38
DLY-18	18W	220-240V AC	140x65 120-130	2200	0.56
DLY-25	25W	220-240V AC	140x65 120-130	2800	0.56
DLY-35	35W	220-240V AC	180x81 160-170	3700	0.88