



DRL

TECHNICAL

Materials of Optics	PC with Glass
Materials of Housing	Die Cut Aluminium
Light Source	COB (SCDM <3)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@4000K	120 Lum/W
CRI	>80
Beam Angle(°)	24/45/60 deg
UGR	<19
Lifetime(hr)	>50,000h
Product Finishing	White


FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Triac
Functions	-
Ingress Protection (IP Rating)	IP20
Impact Resistance (IK Rating)	IK03
Power Factor (PF)	> 0.90

Certification



ACCESSORIES & DIMENSIONS



MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	CUT-OUT(mm)	LUMEN(±5%)	N.W/pc(kgs)
DRL-18	18W	220-240V AC	150x116	130-140	2150	0.71
DRL-25	25W	220-240V AC	150x116	130-140	2800	0.71
DRL-35	35W	220-240V AC	185x130	160-170	3800	1.10
DRL-42	42W	220-240V AC	185x130	160-170	4200	1.10