



DSL

TECHNICAL

Materials of Optics	Polished Aluminium & Glass
Materials of Housing	Die Cast Aluminium
Light Source	COB (SCDM <3)
Color Temperature	2700K/ 3000K/ 4000K/ 5000K
Luminous Efficiency@4000K	110lm/W
CRI	≥80
Beam Angle(°)	15°/24°/36°/60°
UGR	-
Lifetime(hr)	>50,000h
Product Finishing	White

FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Triac
Functions	-
Ingress Protection (IP Rating)	IP20
Impact Resistance (IK Rating)	-
Power Factor (PF)	≥0.9

Certification




MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBmm)	CUT-OUT(mm)	LUMEN(±5%)	N.W/pc(kgs)
DSL-10	10W	AC220-240V	96x68	85x90	1100	0.20
DSL-15	15W	AC220-240V	145x102	120x130	1650	0.60
DSL-20	20W	AC220-240V	145x102	120x130	2200	1.05
DSL-35	35W	AC220-240V	180x128	165x170	3850	1.05
DSL-45	45W	AC220-240V	180x128	165x170	4950	1.05

ACCESSORIES & DIMENSIONS



A

B