



## FLC

### TECHNICAL

Materials of Optics	PC Lens & Glass
Materials of Housing	Made of high pressure die cast aluminum alloy, chemically treated & polyester powder coated.
Light Source	SMD (SCDM <3)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@5000K	120lm/w
CRI	>80
Beam Angle(°)	90 deg
UGR	
Lifetime(hr)	L80 - 90000h
Product Finishing	Silver Grey



### FEATURES & BENEFITS

LED Driver	Built-In
Dimming Option	Dali/1-10V
Functions	-
Ingress Protection (IP Rating)	IP66
Impact Resistance (IK Rating)	IK07
Power Factor (PF)	> 0.95

#### Certification



### MODEL REF.

Standard CCT 5000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	LUMEN(±5%)	N.W/pc(kgs)
FLC-50	50W	220-240V AC	250x231x44	6000	1.5
FLC-100	100W	220-240V AC	347x314x50	12000	3
FLC-150	150W	220-240V AC	398x366x53	18000	4.2
FLC-200	200W	220-240V AC	446x413x55	24000	5.5
FLC-300	300W	220-240V AC	513x477x60	36000	7.7

### Dimensions

