



## FLH

### TECHNICAL

Materials of Optics	PC Lens & Glass
Materials of Housing	Die Cast Aluminium
Light Source	SMD (SCDM <3)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@5000K	180lm/w
CRI	≥80
Beam Angle(°)	90°
UGR	-
Lifetime(hr)	>100000h
Product Finishing	Silver Grey



### FEATURES & BENEFITS

LED Driver	Built-In
Dimming Option	Dali/1-10V
Functions	Power adjustable for different light outputs
Ingress Protection (IP Rating)	IP66
Impact Resistance (IK Rating)	IK08
Power Factor (PF)	> 0.91

#### Certification



### MODEL REF.

Standard CCT 5000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	LUMEN(±5%)	N.W/pc(kgs)
FLH-50	50W	220-240V AC	344x269x65	9000	2.5
FLH-100	100W	220-240V AC	389x317x65	18000	3.7
FLH-150	150W	220-240V AC	419x349x65	27000	4.6
FLH-200	200W	220-240V AC	458x387x65	36000	6.2
FLH-240	240W	220-240V AC	498x441x65	43200	7.6
FLH-300	300W	220-240V AC	498x441x65	54000	8.1

Note : 50W is with PC cover

### Dimensions

