



LDL

TECHNICAL


Materials of Optics	PC
Materials of Housing	Aluminium
Light Source	SMD (SCDM <3)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@4000K	100lm/W
CRI	>80
Beam Angle(°)	90 deg
UGR	
Lifetime(hr)	>50,000h
Product Finishing	White

FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Dali/1-10V
Functions	
Ingress Protection (IP Rating)	IP44
Impact Resistance (IK Rating)	IK01
Power Factor (PF)	> 0.90
Certification	



ACCESSORIES & DIMENSIONS



MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	LUMEN(±5%)	N.W/pc(kgs)
LDL-10	10W	220-240V AC	115x45x90	800	0.20
LDL-13	13W	220-240V AC	129x45x105	1000	0.30
LDL-18	18W	220-240V AC	152x48x125	1300	0.40
LDL-20	20W	220-240V AC	175x52x145	2000	0.40
LDL-25	25W	220-240V AC	203x56x175	2500	0.50
LDL-30	30W	220-240V AC	203x56x175	3000	0.65
LDL-33	33W	220-240V AC	228x63x205	3300	0.65
LDL-40	40W	220-240V AC	228x63x205	4000	0.65