



OD

TECHNICAL


Materials of Optics	PMMA
Materials of Housing	Trimmed sheet steel, chemically treated and electrostatically powder coated
Light Source	SMD (SCDM<6)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@4000K	135 Lum/W
CRI	≥80
Beam Angle(°)	90 deg
UGR	-
Lifetime(hr)	>50,000h
Product Finishing	White

FEATURES & BENEFITS

LED Driver	Built-In
Dimming Option	Dali/1-10V
Functions	Power adjustable for different light output
Ingress Protection (IP Rating)	IP54
Impact Resistance (IK Rating)	IK10
Power Factor (PF)	> 0.90
Certification	



ACCESSORIES & DIMENSIONS



MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	LUMEN(±5%)	N.W/pc(kgs)
OD60-17	17W	220-240V AC	650x107x75	2300	1.7
OD120-22	22W	220-240V AC	1256x107x75	2970	2.2
OD120-30	30W	220-240V AC	1256x107x75	4050	2.2
OD120-44	44W	220-240V AC	1256x107x75	5800	2.2