

# ODRP



## TECHNICAL

Materials of Optics	PC
Materials of Housing	Trimmed sheet steel, chemically treated and electrostatically powder coated
Light Source	SMD (SCDM <3)
Color Temperature	3000K/4000K/5000K
Luminous Efficiency@4000K	120/140/180 lm/W
CRI	≥80
Beam Angle(°)	90°/120°
UGR	(<19 for option)
Lifetime(hr)	>50,000h
Product Finishing	White


## FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Triac/ DALI/ 0-10V
Functions	-
Ingress Protection (IP Rating)	IP44
Impact Resistance (IK Rating)	-
Power Factor (PF)	≥0.9

### Certification



## ACCESSORIES & DIMENSIONS



## MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	CUT-OUT(mm)	LUMEN(±5%)	N.W/pc(kgs)
ODRP3030-10	10W	AC220-240V	295x295x32	280x280	120	0.65
ODRP3060-16	16W	AC220-240V	595x295x32	580x280	120	1.01
ODRP6060-36	36W	AC220-240V	595x595x32	580x580	120	1.56
ODRP60120-60	60W	AC220-240V	1195x595x32	1180x580	120	3.20
ODRP30120-36	36W	AC220-240V	1195x295x32	1180x280	120	1.72/2.05
ODRP6060-30	30W	AC220-240V	595x595x32	580x580	140	1.98/2.35
ODRP30120-30	30W	AC220-240V	1195x295x32	1180x280	140	1.72/2.05
ODRP30120-50	50W	AC220-240V	1195x595x32	1180x580	140	3.20/3.90
ODRP6060-20	20W	AC220-240V	595x595x32	580x580	180	1.56/1.90
ODRP30120-20	20W	AC220-240V	1195x295x32	1180x280	180	1.72/2.05
ODRP60120-40	40W	AC220-240V	1195x595x32	1180x580	180	3.20/3.90