

RLC

TECHNICAL

Materials of Optics	PC
Materials of Housing	Trimmed sheet steel, chemically treated and electrostatically powder coated
Light Source	SMD (SCDM <3)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@4000K	110/120/140 lm/W
CRI	≥80
Beam Angle(°)	100°
UGR	<16
Lifetime(hr)	>50,000h
Product Finishing	White

FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Triac/ DALI/ 0-10V
Functions	-
Ingress Protection (IP Rating)	IP40
Impact Resistance (IK Rating)	-
Power Factor (PF)	≥0.9

Certification




ACCESSORIES & DIMENSIONS



Recessed

Surface mounted

Suspended



MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	CUT-OUT(mm)	LUMEN(±5%)	N.W/pc(kgs)
RLC3060-18	18W	AC220-240V	595x295x36	580x280	2010	1.55
RLC6060-25	25W	AC220-240V	595x595x36	580x580	3552	2.90
RLC6060-30	30W	AC220-240V	595x595x36	580x580	3660	2.90
RLC6060-36	36W	AC220-240V	595x595x36	580x580	3900	2.90
RLC30120-25	25W	AC220-240V	1195x295x36	1180x280	3552	2.95
RLC30120-30	30W	AC220-240V	1195x295x36	1180x280	3660	2.95
RLC30120-36	36W	AC220-240V	1195x295x36	1180x280	3900	2.95