



## RLO

### TECHNICAL

Materials of Optics	PC
Materials of Housing	Trimmed sheet steel, chemically treated and electrostatically powder coated
Light Source	SMD (SCDM <3)
Color Temperature	3000K/ 4000K/ 5000K/ 5700K
Luminous Efficiency@4000K	100lm/W
CRI	≥80
Beam Angle(°)	90°
UGR	<19
Lifetime(hr)	>50,000h
Product Finishing	White


### FEATURES & BENEFITS

LED Driver	Built-out
Dimming Option	Triac/ DALI/ 0-10V
Functions	-
Ingress Protection (IP Rating)	IP20
Impact Resistance (IK Rating)	-
Power Factor (PF)	≥0.9

#### Certification



### ACCESSORIES & DIMENSIONS



### MODEL REF.

Standard CCT 4000K

CODE	WATT	INPUT VOLTAGE(V)	SIZE(AxBxCmm)	CUT-OUT(mm)	LUMEN(±5%)	N.W/pc(kgs)
RLO6060-36	36W	AC220-240V	595x595x40	580x580	3700	2.60
RLO30120-36	36W	AC220-240V	1195x295x40	1180x280	3700	2.99
RLO60120-60	60W	AC220-240V	1195x595x49	1180x580	6500	5.41